

DS-K1104**Pro 1104 Series Metal Vandal-proof Card Reader**

- M1 card reader
- PC+zinc-alloy material shell
- Built-in audible beeper
- RS-485 and Wiegand interface
- IK10

▪ Specification

Authentication	
Card reading frequency	13.56MHz
General	
Power supply	12 VDC, ≤ 500 mA
Power consumption	≤ 2 W
Working temperature	-20 °C to 65 °C (-4 °F to 149 °F)
Working humidity	10% to 90% (no condensing)
Dimensions	118 mm × 76 mm × 23 mm (4.65" × 2.99" × 0.91")
Installation	Applied for 86 & 120 Gang Box
Weight	≤ 0.52 kg (1.1 lb)
Keypad	DS-K1104M: No keypad DS-K1104MK: Keypad with 12 keys (0 to 9, *, #)
Buzzer	Support
Function	
ID settings	via DIP Switch

▪ Available Model

DS-K1104

▪ Accessory

▪ Optional

DS-K7M102-M
M1 Card



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq