

DS-K4H188S

One-Door Magnetic Lock

The DS-K4H188S One-door magnetic lock is designed for wooden door, glass door, and steel door with the opening angle of 90°. The maximum thrust of the lock is 180kg.



AVAILABLE MODEL

DS-K4H188S

MAIN FEATURES

- The magnetic lock supports static linear thrust of 180kg(350Lbs);
- It is equipped with internal voltage dependent resistor (MOV);
- It is applied to wooden door, glass door, metal door and fireproof door;
- Anti-residual magnetism design
- Abrasion-proof materials;
- The shell is made up of aldural and is hard anodizing electroplated;
- No mechanical failure, and the magnetic lock works by electromagnetism force;

SPECIFICATIONS

Model	DS-K4H188S
Dimension of Lock Body (L×W×H)	170×40×22mm
Dimension of Armature Plate (L×W×H)	139×34×10mm
Unlock Method	Current Interruption
Maximum Thrust	180kg(350Lbs) Linear Thrust
Input Voltage	12 VDC
Working Current	300mA
Suitable Door	Wooden Door, Glass Door, Metal Door, Fireproof Door

Model	DS-K4H188S
Surface Temperature	≤ Ambient Teperature +20°C (68°F)
Working Temperature	-10°C~+55°C (14°F~131°F)
Working Humidity	0~95% (Relative Humidity)
Shell	Hard Anodizing Electroplating Operated
Lock Body	Eco-friendly Nickel Electroplating Operated
Armature Plate	Eco-friendly Zinc Electroplating Operated
Weight	1.15kg